

MyStar Specifications

GENERAL	
Operating voltage	100 – 240 VAC
Power consumption	50W
Weight	3.05 kg NET
Dimensions (W x H x D)	360 x 76 x 257.8 mm
UHF modulator	PAL/Ch 21 - 69
Operating temperature range	10 – 45 °C
Storage temperature range	-25 – 70 °C
Hard Disk capacity	160GB total (120GB personal storage)

CONNECTIONS	
Mains input	IEC 83
LNB-IN 1	IEC 60169-24
LNB-IN 2	IEC 60169-24
Terrestrial	IEC 60169-2 female
S-Video Out	EN 60933-5
Aerial In	IEC 60169-2 female
RF Out – 1	IEC 60169-2 male
Audio Out (L and R)	RCA female (IEC 60268-11)
SPDIF	IEC-60958
USB 2.0	USB 2.0
RS-232	9-pin D/DCE
Ethernet	RJ-45/IEEE 802.3

Product compliance



This symbol indicates ‘Dangerous voltage’ in MyStar. It represents the risk of electric shock or bodily injury. Your product complies with the Australian Electrical Safety standard AS/NZ 60065: 2003.



DDP060AUS/T500 – The C-Tick symbol and C-Tick number (N10406) printed on MyStar guarantees that your product complies with the Australian EMC standard AS/NZ CISPR 13: 2004



Manufactured under License from Dolby Laboratories “Dolby” and the double-D symbol are trademarks of Dolby Laboratories.

This product incorporates copyright protection technology that is protected by U.S. patents and other intellectual property rights. Use of this copyright protection technology must be authorised by Macrovision, and is intended for home and other limited viewing uses only unless otherwise authorised by Macrovision. Reverse engineering or disassembly is prohibited.

